

The webbings are used for a temperature range up to 1'000°C. Silica-Glass yarns of variable counts. The fibre diameter exceeds 6µ (no health hazard).

The webbing – system may be chosen according to the specific needs: Canvas single or multiply, with or without binding, atlas, twill, etc.

All webbings are manufactured with woven edges.

The belts may be coated with heat resisting raisins.



Silicabelt

40 mm x 2.0 mm

OUR E-GLASS WEBBINGS ARE CHARACTERISED BY:

- Isolation fabric
- Covers/spark protection
- Conveyor belt
- Fire protection

PRODUCTION PROGRAM:

- Rolls up to 100m in length
- Thickness from 1 mm up to 30 mm
- Hybrid fabrics possible
- Taylor made webbings according to customer specifications
- Maximum width 600 mm



Silicawebbing

500 mm x 8.0 mm

SAMPLE DIMENSIONS:

Article name	Thickness (mm)	Width (mm)							
		> 50	100	150	200	300	400	500	600
Silica-Glassbelt	> 2	✓	✓	✓	✓	✓	✓	✓	✓
Silica-Glassbelt	5	✓	✓	✓	✓	✓	✓	✓	✓
Silica-Glassbelt	6	✓	✓	✓	✓	✓	✓	✓	✓
Silica-Glassbelt	8	✓	✓	✓	✓	✓	✓	✓	✓
Silica-Glassbelt	10	✓	✓	✓	✓	✓	✓	✓	✓
Silica-Glassbelt	12	✓	✓	✓	✓	✓	✓	✓	✓
Silica-Glassbelt	15	✓	✓	✓	✓	✓	✓	✓	✓